

Tyče ocelové kruhové

válcované za tepla - normální a zvýšená přesnost

ČSN 42 5510-1:94


Odpovídající zahraniční normy:

DIN: 1013 T 1:76

Euronorm (EU): 60:77

TDP: ČSN 42 0138:71

ČSN EN 10025:94



Jmen. průměr d	Mezní úchylka při přesnosti		Hmotnost [kg/m]	Jmen. průměr d	Mezní úchylka při přesnosti		Hmotnost [kg/m]		
	norm. A	zvýš. Z			norm. A	zvýš. Z			
5,5	±0,4	±0,3	0,187	47	±0,8	±0,6	13,619		
6			0,222	48			14,205		
7			0,302	50			15,413		
8			0,395	52			16,671		
9			0,499	55			18,65		
10			0,617	56	19,335				
11			0,746	57	20,031				
12			0,888	58	20,74				
13			1,042	60	22,195				
14			1,208	62	23,7				
15			1,387	63	24,47				
16			±0,5	±0,4	1,578	65	±1,0	±0,8	26,049
17					1,782	68			28,509
18					1,998	70			30,21
19					2,226	73			32,855
20	2,466	75			34,68				
21	2,719	78			37,51				
22	2,984	80			39,458				
23	3,261	82			41,456				
24	3,551	85	44,545						
25	3,853	88	47,745						
26	±0,6	±0,5	4,168	90	±1,3	±1,0	49,94		
27			4,495	95			55,643		
28			4,834	100			61,654		
29			5,185	105			67,973		
30			5,549	110			74,601		
31			5,925	115			81,537		
32			6,313	120			88,781		
34			7,127	125			96,334		
35			7,553	130			104,19		
36			±0,8	±0,6			7,99	140	±2,0
37	8,44	150			138,72				
38	8,903	160			157,83				
39	9,377	170			178,18				
40	9,865	180			199,76				
42	10,876	190			222,57				
44	11,936	200			246,62				
45	12,485	210			272				
46	13,046	220			298				
							± 1,5%d	± 1,2%d	