

Tyče ploché


z ocelí tříd 11 a 12 tažené za studena
s úchytkami h11 a h12

ČSN 42 6522:85

Odpovídající zahraniční normy:

DIN: 174:69

TDP: ČSN 42 0134:91



Šířka b [mm]	Tloušťka h [mm]														
	1,6	2	2,5	3	4	5	6	8	10	12	16	20	25	32	
	Mezní úchytky h 11 (h12)														
	-0,06 (- 0,100)				-0,075 (- 0,120)			-0,090 (- 0,150)		-0,110 (- 0,180)		-0,130 (- 0,210)		-0,250 -	
Hmotnost [kg/m]															
5	0,063	0,079	0,098	0,118	-	-	-	-	-	-	-	-	-	-	
6	-	0,094	0,118	0,141	0,188	-	-	-	-	-	-	-	-	-	
8	0,1	0,126	0,157	0,188	0,251	0,314	0,377	-	-	-	-	-	-	-	
10	0,126	0,157	0,196	0,236	0,314	0,393	0,471	0,628	-	-	-	-	-	-	
12	-	0,188	0,236	0,283	0,377	0,471	0,565	0,754	0,942	-	-	-	-	-	
14	-	0,22	0,275	0,33	0,44	0,55	0,659	0,879	1,099	1,319	-	-	-	-	
16	-	0,251	0,314	0,377	0,502	0,628	0,754	1,005	1,256	1,507	-	-	-	-	
18	-	0,283	0,353	0,424	0,565	0,707	0,848	1,13	1,413	1,696	2,261	-	-	-	
20	-	0,314	0,393	0,471	0,628	0,785	0,942	1,256	1,57	1,884	2,512	-	-	-	
22	-	-	0,432	0,518	0,691	0,864	1,036	1,382	1,727	2,072	2,763	3,454	-	-	
25	-	-	0,491	0,589	0,785	0,981	1,178	1,57	1,963	2,355	3,14	3,925	-	-	
28	-	-	-	0,659	0,879	1,099	1,319	1,758	2,198	2,638	3,517	4,396	5,495	-	
32	-	-	-	-	1,005	1,256	1,507	2,010	2,512	3,014	4,019	5,024	6,28	-	
36	-	-	-	-	1,13	1,413	1,696	2,261	2,826	3,391	4,552	5,652	7,065	9,043	
40	-	-	-	-	1,256	1,57	1,884	2,512	3,14	3,768	5,024	6,28	7,85	10,05	
45	-	-	-	-	1,413	1,766	2,12	2,826	3,533	4,239	5,652	7,065	8,831	11,3	
50	-	-	-	-	1,57	1,963	2,355	3,14	3,925	4,71	6,28	7,85	9,813	12,56	
56	-	-	-	-	1,758	2,198	2,638	3,517	4,396	5,275	7,034	8,792	10,99	14,07	
63	-	-	-	-	-	2,473	2,967	3,956	4,946	5,935	7,913	9,891	12,36	15,83	
70	-	-	-	-	-	2,478	3,297	4,396	5,495	6,594	8,792	10,99	13,74	17,58	
80	-	-	-	-	-	-	3,768	5,024	6,28	7,536	10,05	12,56	15,7	20,1	
90	-	-	-	-	-	-	4,239	5,652	7,065	8,478	11,3	14,13	17,66	22,61	
100	-	-	-	-	-	-	-	6,28	7,85	9,42	12,56	15,7	19,62	25,12	