

Tenkostěnné profily

ocelové otevřené průřezu L nerovnoramenné


JN 42 6962:95 (ČSN 42 6950:86)

Odpovídající zahraniční normy:

DIN: 59413:76

TDP: JN 42 0121:95

(ČSN 42 0121:77)



Jmen. rozměry [mm]			Hmotnost	Jmen. rozměry [mm]			Hmotnost
h	b	t	[kg/m]	h	b	t	[kg/m]
12	10	1,5	0,224	40	20	3	1,295
14	4	1	0,126	40	25	2	0,973
15	10	1,5	0,259	40	25	3	1,413
15	10	2	0,345	40	30	2	1,052
15	10	2,5	0,412	40	30	3	1,531
18	12	1,5	0,318	40	35	2,5	1,393
18	12	2	0,424	40	35	3	1,649
20	10	1,5	0,318	43	17	3,5	1,295
20	10	2	0,424	45	10	2	0,816
20	12	2	0,455	45	25	2	1,052
20	15	2	0,502	45	35	2,5	1,492
20	15	3	0,707	45	35	3	1,766
22	18	2	0,581	45	40	3	1,884
25	10	2	0,502	50	20	2	1,052
25	12	2	0,534	50	20	3	1,531
25	15	1,5	0,436	50	25	2	1,13
25	15	2	0,581	50	25	3	1,649
25	15	3	0,824	50	30	3	1,766
25	20	2	0,659	50	35	2	1,287
28	20	2	0,707	50	40	2	1,366
30	10	2	0,581	55	20	4	2,135
30	15	2	0,659	55	25	3	1,766
30	20	2	0,738	60	20	2	1,209
30	20	3	1,06	60	25	2	1,287
30	20	4	1,35	60	25	3	1,884
30	25	2	0,816	60	30	3	2,002
30	25	3	1,178	60	40	2	1,523
35	10	2	0,659	60	40	3	2,237
35	14	2	0,707	60	40	4	2,842
35	15	2	0,738	60	40	5	3,611
35	15	3	1,06	65	35	3	2,237
35	20	2	0,816	70	20	2	1,366
35	25	1,5	0,671	70	40	2	1,68
35	25	2	0,895	70	45	5	4,2
35	25	3	1,295	70	50	2	1,837
35	30	2	0,973	70	50	3	2,708
40	12	2	0,769	75	52	2	1,931
40	15	2	0,816	75	52	2,5	2,414
40	15	3	1,178	75	52	3	2,873
40	20	1,5	0,671	85	25	2,5	2,08
40	20	2	0,895	104	40	3	3,273
40	20	2,5	1,099				